








COMPACT GRADE LAMINATE (CGL) STANDARD COLORS & PATTERNS

Single Piece Panels Available Up To 5'



Satin Stainless with Dove Grey Core 4830-SC-60SC*




Evening Tigris 4674-60



Satin Stainless with Black Core 4830-60



Citadel Warp 5882-58



White 949-58



Navy Grafix 7018-58



Grey Grit P-886-CA



Graphite Grafix 515-58




Pewter Mesh 4878-60

Black Stone

P-500-CA



Earth 5342-58



Black 1595-60

Single Piece Panels Available Up To 6'**



Ice White 410-SEI



Silvretta 0229-FH



Sand 414-SEI

Cello

0811-FH



Light Grey 478-SEI



Pearl Grey 475-SEI



Brushed Aluminum 0328-FH



Charcoal 0077-FH

Additional Colors: Solid Color CGL - Wilsonart® Solicor™ Colors & Patterns*

Note: Non-stock; made to order, lead times and color upcharge premiums apply. Samples can be requested from the manufacturer.

Designer White D354-SC-60SC (White Core)



Dove Grey D92-SC-60SC



Silver Oak Ply 8203-SC-60SC



Pressed Linen 4991-SC-60SC



Silver Alchemy 4860-SC-60SC







High Line 7970-SC-60SC



Phantom Ecru 8212-SC-60SC



Park Flm



Tan Soapstone 4887-SC-60SC





Field Flm 7999-SC-60SC






4990-SC-60SC





^{*}Wilsonart* SOLICOR™ is a specialty laminate with a solid color core to match the surface. Color upcharge premium applies

Hundreds of additional CGL colors are available from our partners; additional lead time will apply. Please consult with ABET LAMINATI*, ARBORITE*, FORMICA*, Wilsonart* or FUNDERMAX for color options. Non-stock Abet Laminati or FUNDERMAX colors carry a significant lead time of 10-14 weeks.





^{*}Wilsonart* SOLICOR™ is a specialty laminate with a solid color core to match the surface. Color upcharge premium applies.

^{**}Standard color by ABET LAMINATI and FUNDERMAX* allows for single panel width up to 72", eliminating use of additional hardware. Meets Class A fire rating without

MATERIAL OVERVIEW

Scratch, Dent and Graffiti Resistance


Compared to competitive materials, Bobrick materials perform exceptionally well for scratch, dent and graffiti resistance when subjected to industry-standard ASTM test protocols. Consider the relative price of Bobrick's high performance substrates and it's clear: Bobrick materials are the pinnacle of value.

	Material	Price Index	Scratch Resistance ASTM D 2197 Weight Required to Scratch	Impact Resistance ASTM D 2794 Visible Damage, Inches-Pounds Per Force (lbf)	Graffiti Resistance ASTM D 6578 Marks Removed (Out of 6)	Interior Finish Classification ASTM E 84
Bobrick Material	Compact Grade Laminate (CGL) (Black Core)	\$\$-\$\$\$	>10kg	168" -Ibf	5	Class A or B
Other Manufacturers' Materials	Powder-Coated Metal	\$	<0.5kg	2" -lbf	4	Class A
	Plastic (HDPE)	\$\$	<0.5kg	<1" -lbf	3	In 48 states and Washington, D.C., ASTM E 84 is not the relevant test. Must pass an unmodified NFPA 286 test.
	Stainless Steel	\$\$\$\$\$	1.0kg	2" -lbf	5	Class A

Bobrick Material



Compact Grade Laminate (CGL)



Other Manufacturers' Materials



Powder-Coated Metal



Plastic (HDPE)



Stainless Steel

Material Specification:

Solidly fused plastic laminate with matte-finish melamine surfaces; integrally bonded colored face sheets and black phenolic-resin core. Wilsonart® SOLICOR $^{\text{TM}}$ color-through CGL also available with core to match surface.

- · Scratch, moisture, impact and graffiti resistant
- Class A or B ASTM E 84 classification
- Wide selection of colors and patterns

Available on: Evolve Cubicles, Traditional DuraLineSeries®